ZIRKOL – L

ZIRKOL – L is a family of linear suspension lamps suitable for general and decorative lighting.
Anodized aluminium body and opal screen to a homogeneous lighting. Light emission can be direct light and double light emission with high flux and different colour temperatures. Driver and dimmer interface included.

LINEAR 39.4" | DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	14.5W
Emission	Diffused orientable
Switching	0-10V
Tension	110/240V
Color temperature	2700K
Luminous flux	833lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 x adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled





Codes	*Structure*
UZRL1610G15DBO	matt white
UZRL1610G15DNE	matt black
UZRL1610G15DOR	matt gold

Certificazioni

Intertek

LINEAR 39.4" | DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	14.5W
Emission	Diffused orientable
Switching	0-10V
Tension	110/240V
Color temperature	3000K
Luminous flux	882lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 x adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled

Codes	*Structure*
UZRL1610G15WBO	matt white
UZRL1610G15WNE	matt black
UZRL1610G15WOR	matt gold

Certificazioni





LINEAR 39.4" | DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	14.5W
Emission	Diffused orientable
Switching	0-10V
Tension	110/240V
Color temperature	4000K
Luminous flux	980lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 x adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled





Codes	*Structure*
UZRL1610G15NBO	matt white
UZRL1610G15NNE	matt black
UZRL1610G15NOR	matt gold

Certificazioni

Intertek

LINEAR 39.4" | UP-DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	29W
Emission	Diffused orientable
Switching	0-10V
Tension	110/240V
Color temperature	2700K
Luminous flux	1666lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled





Codes	*Structure*
UZRL1710G15DBO	matt white
UZRL1710G15DNE	matt black
UZRL1710G15DOR	matt gold

Certificazioni

Intertek

LINEAR 39.4" | UP-DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	29W
Emission	Diffused orientable
Switching	0-10V
Tension	29W
Color temperature	3000K
Luminous flux	1764lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled





Codes	*Structure*
UZRL1710G15WBO	matt white
UZRL1710G15WNE	matt black
UZRL1710G15WOR	matt gold

Certificazioni

Intertek

LINEAR 39.4" | UP-DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	29W
Emission	Diffused orientable
Switching	0-10V
Tension	110/240V
Color temperature	4000K
Luminous flux	1960lm
Typ CRI	90
IP class	IP40
Dimensions	39.4"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled





Codes	*Structure*
UZRL1710G15NBO	matt white
UZRL1710G15NNE	matt black
UZRL1710G15NOR	matt gold

Certificazioni

Intertek

LINEAR 78.7" | DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	29W
Emission	Diffused orientable
Switching	0-10V
Tension	110/240V
Color temperature	2700K
Luminous flux	1666lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled





Codes	*Structure*
UZRL1620G15DBO	matt white
UZRL1620G15DNE	matt black
UZRL1620G15DOR	matt gold

Certificazioni

Intertek

LINEAR 78.7" | DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	29W
Emission	Diffused orientable
Switching	0-10V
Tension	110/240V
Color temperature	3000K
Luminous flux	1764lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled

Codes	*Structure*
UZRL1620G15WBO	matt white
UZRL1620G15WNE	matt black
UZRL1620G15WOR	matt gold

Certificazioni





LINEAR 78.7" | DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	29W
Emission	Diffused orientable
Switching	0-10V
Tension	110/240V
Color temperature	4000K
Luminous flux	1960lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled

Codes	*Structure*
UZRL1620G15NBO	matt white
UZRL1620G15NNE	matt black
UZRL1620G15NOR	matt gold

Certificazioni





LINEAR 78.7" | UP-DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	58W
Emission	Diffused orientable
Switching	0-10V
Tension	110/240V
Color temperature	2700K
Luminous flux	3332lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled





Codes	*Structure*
UZRL1720G15DBO	matt white
UZRL1720G15DNE	matt black
UZRL1720G15DOR	matt gold

Certificazioni

Intertek

LINEAR 78.7" | UP-DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	58W
Emission	Diffused orientable
Switching	0-10V
Tension	110/240V
Color temperature	3000K
Luminous flux	3528lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled

Codes	*Structure*
UZRL1720G15WBO	matt white
UZRL1720G15WNE	matt black
UZRL1720G15WOR	matt gold

Certificazioni



LINEAR 78.7" | UP-DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	58W
Emission	Diffused orientable
Switching	0-10V
Tension	110/240V
Color temperature	4000K
Luminous flux	3920lm
Typ CRI	90
IP class	IP40
Dimensions	78.7"x1.9"
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 electrical cable length 16.4' | 2 adjustable metal cable length 9.8' (including ceiling attachments). RAL 9005 black | RAL 9016 white | shipped assembled





Codes	*Structure*
UZRL1720G15NBO	matt white
UZRL1720G15NNE	matt black
UZRL1720G15NOR	matt gold

Certificazioni

Intertek